



Version: 1.0, July 16, 2018

## THINKPAD P71

### Product Overview

The ThinkPad P71 redefines the concept of power with an Intel® Xeon™ processor and NVIDIA Quadro graphics. Feature-packed with optional X-Rite® PANTONE® color calibration, Mil-Spec durability, blazing-fast connection speeds, and the highest capacity of storage and memory make this workstation your go-to PC for getting the job done.

### Operating Systems

#### Preloaded

Genuine Windows 10® Professional 64-bit

Genuine Windows 10DG to 7® Professional 64-bit

Ubuntu Linux

#### Supported

Red Hat Enterprise Linux 7.3

### Motherboard - P71

### Chassis Summary

#### Chassis Information

Dimensions	29.90mm (1.18in) x 416mm (16.38in) x 275.50mm (10.85in)
Weight	Starting at 7.5lbs
Packaging Parameters without External Speaker	
Color	ThinkPad Business Black
PSU	170W, 2pin
Thermal Solutions	Dual Fan, 1 dedicated CPU, 1 dedicated GPU with connected heat sinks

### Physical Security & Serviceability

Hardware Maintenance Manual [Click Here](#)

User Guide [Click Here](#)

Drivers & Software [Click Here](#)

Access Panel	Bottom cover, 6 screws
Hard Drives	Screw, 1x
Memory	Tool-less
Restore CD/DVD Set	Restore system to original factory shipping image - Can be obtained via Lenovo Support
Cable Lock Support	Yes, Optional Kensington Cable Lock
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes
Power-On Password	Yes
Setup Password	Yes
NIC LEDs (integrated)	Yes
Security Chip	Yes, TCG dTPM 2.0
Boot Sequence Control	Yes

## Operating Environment

### Air Temperature

- 8,000ft (2438m)
- Operating without a drive installed: 5°C to 35°C (41°F to 95°F)
- Operating with a drive installed: 10°C to 35°C (50°F to 95°F)
- Non-operating: 5°C to 31.3°C (41°F to 88°F)
- 10000ft (3048m)
- Operating unpressurized Condition: 5°C to 31.3°C (41°F to 88°F)

### Storage

- \*-20°C to 60°C (-4°F to 140°F)

### Humidity

- Operating 8% ~ 95% (non-condensing)
- Non-Operating 5% ~ 95%(non-condensing)

## Environmental Certifications

- Energy Star 6.1
- EPEAT Gold
- GreenGuard Gold
- TCO 5.0

## Hazardous Substances

- Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenol ethers (PBDE).
- Products do not contain Asbestos.
- Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide.
- Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparation.
- Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the

## SCCP

- Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm<sup>2</sup>/week.

## SECTION II: SUPPORTED COMPONENTS

### CPU Specifications

#### Intel 6th Gen Core and Xeon CPUs

[www.ark.intel.com](http://www.ark.intel.com)

Intel® Core™ i7-6700HQ processor (6MB L3, Up to 3.5GHz)

Intel® Core™ i7-6820HQ vPro processor (8MB L3, Up to 3.6GHz)

Intel® Xeon™ E3-1505M v5 vPro processor (8MB L3, Up to 3.7GHz)

Intel® Xeon™ E3-1535M v5 vPro processor (8MB L3, Up to 3.8GHz)

### Memory Specifications

#### P71

Type SODIMM

Speed 2400MHz

Slots 4

Generation DDR4

Capacities - Non-ECC 8GB, 16GB

Capacities - ECC (Only with Xeon CPUs) 8GB, 16GB

Dual Channel Capable Yes

### Storage

2x M.2 for SSD's, 2x 1 HDD, (1HDD w/tray or optical via optical bay)

### RAID

Supported RAID levels for a system will vary from the stated capabilities of the RAID controller due to dependencies on the number and capacity of physical disks in the system and on customer requirements for performance, fault tolerance, or data redundancy. Max support RAID 0,1

#### RAID levels and requirements:

- RAID 0 (striping) provides increased performance by writing data across multiple drives.
- RAID 1 (mirroring) provides fault tolerance by writing the data on two drives.

### Keyboard

- 6 row; spill resistant; Multimedia Fn keys, numeric keypad, optional LED backlight, 2.2mm key stroke, 19.05mm key pitch

### Pointing Devices

- Trackpoint with left/right click and scroll lock, Touchpad with left/middle/right click

### Fingerprint Reader

- Touch Style, match-on-system

## Color Calibrator

- X-Rite Pantone software, AMS RGB sensor

## Graphics Cards

Integrated Graphics

Core CPU: Intel HD 630

Xeon CPU: Intel HD P630

Discrete Graphic Cards

NVIDIA M620 with 2GB GDDR5

NVIDIA P3000 with 6GB GDDR5

NVIDIA P4000 with 8GB GDDR5

NVIDIA P5000 with 16GB GDDR5

## Network

Connector

RJ-45

Model

Intel, I219-V, Intel, I219-LM

Website

[I219-V](#)

[I219-LM](#)

## Miscellaneous

Thunderbolt

Intel Alpine Ridge controller, 1 port via USB Type C, max I/O of 40Gb/s

USB

4x USB Type A (1 powered), 1x USB Type C (support for Thunderbolt 3)

Audio Devices

HD Audio, Realtek ALC3268 codec, Stereo speakers, 2x 1.5W

WiFi Card

Intel Snowfield Peak 8265 2\*2ac+BT4.1 vpro  
Intel Snowfield Peak 8265 2\*2ac+BT4.1 non-vpro

WWAN

US,CA: Sierra EM7455 LTE (HSPA+/GSM/EDGE)  
EU: Sierra EM7455 LTE (HSPA+/GSM/EDGE)

Express Card

34mm

Chassis Materials

A Cover - GFRP  
B Cover - PC/ABS  
C Cover - PC/ABS  
Roll Cage - Mg/Al  
D Cover - Mg/Al

## SECTION III: SYSTEM TECHNICAL SPECIFICATIONS

### Social and Environmental Responsibility

#### Quality Control

- Lenovo is a member of an eco declaration system that enforces regular independent quality control

#### Hazardous substances and preparation

- Products do comply with current European RoHS Directive.

- Products do not contain Asbestos
- Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide
- Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparation
- Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP
- Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 µg/cm<sup>2</sup> /week
- REACH Article 33 information about substances in articles is available at (add URL or mail contact):[http://www.lenovo.com/social\\_responsibility/us/en/materials.html](http://www.lenovo.com/social_responsibility/us/en/materials.html)

## Batteries

- If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual
- Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium
- Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium.
- Batteries and accumulators are readily removable.

## Product packaging

- Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together.
- The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used.
- The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol

For more information on Lenovo social environmental practices

visit: [http://www.lenovo.com/social\\_responsibility/us/en/ThinkGreen\\_products.html#environment](http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment)

## Manageability

Industry Standard Specifications	This product meets the following industry standard specifications for manageability functionality:  Intel LAN with AMT
Remote Manageability Software Solutions	Lenovo ThinkPad is supported on the following remote manageability software consoles:  Lenovo ThinkManagement Console  <a href="http://www.landesk.com/lenovo">LANDesk Management Suite for ThinkVantage Technologies (www.landesk.com/lenovo)</a>  Microsoft System Center Configuration Manager
System Software Manager	Lenovo ThinkPad supports software management tools from the ThinkVantage System Update suite:  System Update

Update Retriever

Thin Installer

Service, Support, and Warranty

On-site Warranty and Service: Up to four-years, limited warranty and service offering delivers on-site, next business-day service for parts and labor and includes free telephone support 8am - 5pm. Global coverage ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.

[Go to www.lenovo.com/support](http://www.lenovo.com/support) and [www.lenovo.com/warranty](http://www.lenovo.com/warranty) for more details

## SECTION IV: COMPONENT SPECIFICATIONS

### Display

Model	17.3" FHD/IPS	17.3" UHD/IPS
Screen Size	17.3"	17.3"
Aspect Ratio	16:09	16:09
Resolution	FHD (1920 x 1080)	UHD (3840 x 2160)
Outline Dimension	398.1 x 250.5mm typ (H x V) Thickness 4.0mm max	398.1 x 254.6mm typ (H x V) Thickness 4.0mm max
Brightness	300 cd/m2	300 cd/m2
Contrast	800:01:00	800:01:00
Viewing Angle (*1)	85/85/85/85degree	85/85/85/85degree
Panel Technology	IPS	IPS
Color Depth	Native 262K (RGB 6-bit data driver)	Native 16.7M (RGB 8-bit data driver)
Interface	eDP 1.2	eDP 1.3
Panel ID recognition	EDID in BIOS table	EDID in BIOS table
Weight	560 grams max	700 grams typ

### HDD Specifications

2.5" SATA HDD	500GB 7200RPM, 6Gb/s
	1TB 5400RPM, 6Gb/s

### SSD Specifications

M.2 PCIe SSD	256 GB, PCIe NVMe, Gen3x4 (MLC), OPAL
	512 GB, PCIe NVMe, Gen3x4 (MLC), OPAL
	256 GB, PCIe NVMe, Gen3x4 (TLC), OPAL
	512 GB, PCIe NVMe, Gen3x4 (TLC), OPAL
	1TB, PCIe NVMe, Gen3x4 (TLC), OPAL

### Graphics Cards

Model	M500M	M600M	M1000M	M2000M	M3000M
-------	-------	-------	--------	--------	--------

<b>TGP (GPU + VRAM)</b>	18W	30W	45W	55W	75W
<b>Video Ram Max</b>	2GB	2GB	4GB	4GB	4GB
<b>Memory type</b>	DDR3	GDDR5	GDDR5	GDDR5	GDDR5
<b>Memory bit</b>	64 bit	128bits	128bits	128bits	192bits
<b>Memory Bandwidth</b>	14.4Gb/s	80GB/s	80GB/s	80GB/s	160GB/s
<b>VRAM Type</b>	2GB	2GB	4GB	4GB	4GB
<b>GPU Cuda Cores</b>	384	384	512	630	1024
<b>DisplayPort Max Resolution &amp; Color Depth</b>	3840×2160 @ 60Hz (30bpp)	3840×2160 @ 60Hz (30bpp)	3840×2160 @ 60Hz (30bpp)	3840×2160 @ 60Hz (30bpp)	3840×2160 @ 60Hz (30bpp)
<b>HDMI Max Resolution &amp; Color Depth</b>	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)
<b>DirectX</b>	12	12	12	12	12
<b>OpenGL</b>	4.4	4.4	4.4	4.4	4.4
<b>OpenCL</b>	1.1	1.1	1.1	1.1	1.1
<b>Optimus</b>	Yes	Yes	Yes	Yes	Yes
<b>OS Support</b>	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu
<b>Model</b>	M4000M	M5000M	M520	M620	M1200
<b>TGP (GPU + VRAM)</b>	100W	100W	25W	30W	45W
<b>Video Ram Max</b>	4GB	8GB	2GB	2GB	4GB
<b>Memory type</b>	GDDR5	GDDR5	GDDR5	GDDR5	GDDR5
<b>Memory bit</b>	256 bits	256 bits	64 bit	128bits	128bits
<b>Memory Bandwidth</b>	160GB/s	160GB/s	40GB/s	80GB/s	80GB/s
<b>VRAM Type</b>	8GB	8GB	2GB	2GB	4GB
<b>GPU Cuda Cores</b>	1280	1536	384	512	640
<b>DisplayPort Max Resolution &amp; Color Depth</b>	3840×2160 @ 60Hz (30bpp)	3840×2160 @ 60Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 60Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 60Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 60Hz (30bpp)
<b>HDMI Max Resolution &amp; Color Depth</b>	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)
<b>DirectX</b>	12	12	12	12	12

OpenGL	4.4	4.4	4.5	4.5	4.5
OpenCL	1.1	1.1	1.2	1.2	1.2
Optimus	Yes	Yes	Yes	Yes	Yes
OS Support	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu
Model	M2200	P710	P3000	P4000	P7100
TGP (GPU + VRAM)	55W	TDP 18W / TDP 2W	75W	100W	100W
Video Ram Max	4GB	2GB	6GB	8GB	16GB
Memory type	GDDR5	GDDR5	GDDR5	GDDR5	GDDR5
Memory bit	128bits	64 Bit	192bits	256 bits	256 bits
Memory Bandwidth	88GB/s	40.1GB/s	168GB/s	192GB/s	192GB/s
VRAM Type	4GB	2GB	4GB	8GB	8GB
GPU Cuda Cores	1024		1280	1920	2304
DisplayPort Max Resolution & Color Depth	Max: 5.4Gb/s ,4 lanes,36bpp 3840×2160 @ 24Hz (30bpp)		Max: 8.1Gb/s, 4 lanes,36bpp 5120×3200 @ 60Hz(24bpp, 30bpp with 422)	Max: 8.1Gb/s, 4 lanes,36bpp 5120×3200 @ 60Hz(24bpp, 30bpp with 422)	Max: 8.1Gb/s, 4 lanes,36bpp 5120×3200 @ 60Hz(24bpp, 30bpp with 422)
HDMI Max Resolution & Color Depth	4096×2160@60Hz RGB888	N/A	4096×2160@60Hz RGB888	4096×2160@60Hz RGB888	4096×2160@60Hz RGB888
DirectX	12	12	12	12	12
OpenGL	4.5	4.5	4.5	4.5	4.5
OpenCL	1.1	1.1	1.1	1.1	1.1
Optimus	Yes	Yes	Yes	Yes	Yes
OS Support	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu	Win10, Win8.1, Win7, Ubuntu

## Networking

### Ethernet

Connector		RJ-45	RJ-45
Model		Intel, I219-V	Intel, I219-LM
Website		<a href="#">Intel-Ethernet-Connection-I219-V</a>	<a href="#">Intel-Ethernet-Connection-I219-LM</a>
10BASE-T (IEEE 802.3 specification conformance)	x	x	x
100BASE-TX (IEEE 802.3 specification conformance)	x	x	x



1000BASE-T (IEEE 802.3 specification conformance)	x	x
Auto-Negotiation (IEEE 802.3u)	x	x
Intel® vPro™ 2 technology		x
Intel® Stable Image Platform Program (SIPP)		x
Intel® Standard Manageability	x	x
Power optimizer platform low-power management systems	x	x
Energy Efficient Ethernet1 (IEEE 802.3az)	x	x
TCP/UDP checksum and segmentation offload (IPv4 and IPv6)	x	x
Receive Side Scaling	x	x
Dual Tx and Rx queues	x	x
Jumbo Frames (up to 9 KB)	x	x
Teaming	x	x
Integrated Auto Connect Battery Saver (ACBS) battery savings	x	x
Timing and Synchronization (802.1as / 1588)	x	x
Integrated Switched Voltage Regulator (iSVR)	x	x
Shared Flash with system BIOS	x	x
Wake from Deep Sx	x	x
Server operating system support		x
Network proxy/ARP support	x	x
32 wake filter support	x	x

## WLAN

Model	Intel 8265
Dimensions	(H x W x D) M.2 2230: 22 mm x 30 mm x 2.4 mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16 mm x 1.8 mm
Weight	M.2 2230: 2.6g M.2 1216: 0.6g
Antenna Diversity	Supported
Radio ON/OFF Control	Supported
Connector interface	M.2: PCIe, USB, or UART (M.2 1216 only)
Operating Temperature (Adapter Shield)	0°C to +80°C
Humidity Non-Operating	50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)
Operating Systems	Microsoft Windows 7*, Microsoft Windows 8.1*, Microsoft Windows 10*, Linux* (limited featuresupport), Android

<b>Wi-Fi Alliance</b>	Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM-PS*, WPA*, WPA2*, WPS2*, Protected Management Frames, Wi-Fi Direct* for peer to peer device connections, Wi-Fi Miracast* as Source.
<b>IEEE WLAN Standard</b>	IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending OS support; Fine Timing Measurement based on 802.11REVmc
<b>Roaming</b>	Supports seamless roaming between access points
<b>Bluetooth*</b>	Dual Mode Bluetooth* 4.2, BLE
<b>Authentication</b>	WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA
<b>Authentication Protocols</b>	WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA
<b>Encryption</b>	64-bit and 128-bit WEP, AES-CCMP
<b>Regulatory</b>	For a list of country approvals, please contact your local Intel representatives.
<b>US Government</b>	FIPS11 ,FISMA;
<b>Product Safety</b>	UL, C-UL, CB (IEC 60950-1)

## WWAN

Model Qualcomm Snapdragon X7 LTE-A (Sierra Wireless EM7455)

### 4G LTE

Category Cat-6

Frequency Bands B1-B5, B7, B12, B13, B20, B25, B26, B29, B30, B41

### 3G

Frequency Bands HSPA+, UMTS  
B1, B2, B3, B4, B5, B8

### Data Speed

Peak Download Rate 300Mbps

Peak Upload Rate 50Mbps

### Location Solution

Satellite Systems GPS, Glonass, Beidou, Galileo

### Audio Codecs

PCM/125 x

### USB Drivers

Windows 7, 8.1, 10 x

Linus x

Android RIL x

### Interfaces

USB USB 3.0, USB 2.0 High Speed

SIM Interface 1.8V/3V x

### Control Options

APIs, AT Commands x

**Hardware**

Dimension 42 x 30 x 2.3mm

**Antenna**

Connector: Main, Aux/GNSS, GNSS x

Diversity x

MIMO x

GNSS Bina x

**Temperature Range**

Industrial Grade \*-40 - 85C

**Approvals**

Regulatory CD, FCC, GCF, IC, NCC, PTCRB

Carrier AT&amp;T, Bell, Rogers, Sprint, Telus, US Cellular, Verizon, Vodafone

**Cloud Services**

Free Unlimited FOTA Upgrades x

Device Management Option x

Application Enablement Option x

Connectivity Management Option x

**Color Calibrator**

Module ECCM-3

Connector USB 2.0

Power Operation - 24mA  
Suspend - 0.5mA

Color Standard CIE 1931

**Colorimetric Accuracy**

Screen Color	Chromaticity Accuracy Limit ( $\Delta x$ , $\Delta y$ ) difference from average reference	Luminance Accuracy Limit (Percent Difference from average reference)
White	+/-0.007	+/-5%
Operating Temp - C	10 - 35	
Humidity %	10 - 95	

**Camera**

Resolution 1280 x 720

Frames per Second 30

Focus Fixed

Low Light Sensitive Yes

