

Lenovo ThinkStation P920

Version: 4 | 08/21/2020

DOWNLOADS

Hardware Maintenance Manual	P920 HMM
Drivers & Software	P920 Drivers & Software
Available Whitepapers	RTX GPU Support Matrix P920/P720 Power Configurator P920/P720 Memory Configurations Intel VROC Support To access additional whitepapers visit https://support.lenovo.com and select 'PC' then 'Workstations'

SECTION I: Platform Overview

Description	The Lenovo ThinkStation P920 is an Intel based high performance dual socket workstation, providing excellent performance and quality for applications where processor, memory, graphics, and storage requirements are critical. The P920 is positioned above the single socket P520 and dual socket P720 workstations.
-------------	--

CPU

Processor Support	Xeon Scalable Processors (Platinum, Gold, Silver, Bronze)
Socket Type	Socket-P0 (LGA 3647)
Preloaded	Windows 10 Pro 64-bit for Workstations Ubuntu 16.04 LTS (configuration specific) Ubuntu 18.04 LTS (configuration specific) Ubuntu 20.04 LTS (configuration specific)
Supported	Windows 7 Pro 64 (via Windows 10 Pro Downgrade Rights) Red Hat Enterprise Linux 7.3 Red Hat Enterprise Linux 8.2 Ubuntu 16.04 LTS

Ubuntu 18.04 LTS Ubuntu 20.04 LTS

Memory

Slots	Up to 16 DIMMs
Channels	Each Processor Supports up to 8 DIMM Sockets, 6 Channels per CPU
Type	288-Pin, 1866/2133/2400/2666/2933MHz ECC RDIMM and LRDIMMS
ECC Support	Yes
Speed	Up to 2933MHz
Max DIMM Size	256GB DDR4 ECC 3DS-RDIMM
Max System Memory	2TB

Storage

SATA	10 x SATA Connectors, Gen 3
PCIe	2 x M.2 PCIe Connectors Onboard
SAS	Supported via Optional Broadcom Adapter
eSATA	1 x eSATA Connector, Gen 3

Video

Integrated Graphics	Not Available
Discrete Graphics	PCIe Add-In-Card, Details in Section Below
Multi-GPU Support	Yes
Type	PCIe Add-In-Card
Bus Interface	PCIe x16

Slots

Slot 1	PCIe 3.0 x16, Full Height, Full Length, 75W, With Latch
Slot 2	PCIe 3.0 x4, Full Height, Full Length, 25W, Open Ended
Slot 3	PCIe 3.0 x16, Full Height, Full Length, 75W, With Latch
Slot 4	PCIe 3.0 x4, Full Height, Full Length, 25W, Open Ended
Slot 5	PCIe 3.0 x4, Full Height, Half Length, 25W, Open Ended
Slot 6	PCIe 3.0 x16, Full Height, Half Length, 75W, With Latch Note - Full Length Supported if Onboard M.2 Slots Not Utilized

Slot 7	PCIe 3.0 x16, Full Height, Full Length, 75W, With Latch
Slot 8	PCIe 3.0 x16, Full Height, Full Length, 75W, With Latch

Front I/O

USB	4 x USB 3.1 Gen 1 Type-A (includes one 15W charging port)
Audio	1 x Combo Audio/Microphone Jack (3.5mm)
Media Card Reader	Front 9-in-1 Media Card Reader Standard (USB 2.0) Optional: Front 15-in-1 Media Card Reader (requires Flex module)
Flex Module	Flex Module: Supports Two 5.25" Flex Bays With Several Options Integrated <ul style="list-style-type: none"> • Up to Two Half Height Optical Drives • Up to Two 5.25" Slim Optical Drive Cages • Up to One Front Access Storage Enclosure • Up to One Flex Module for One or More of the Following Options: 9.0mm Optical/15-in-1 USB 3.1 Gen 1 Reader/Front eSATA/Dual Port Front Thunderbolt/front USB 3.1 Gen 1 Type-C/ 4-Digit Diagnostic Display Note: 1. Only one can be supported from 15-in-1 reader, Thunderbolt, and 4-digit display 2. Up to two ports are supported from 1394, eSATA, and USB Type-C

Rear I/O

USB	2 x USB 2.0 Type-A 4 x USB 3.1 Gen 1 Type-A
Audio	3 x Rear (Line Out, Line In, MIC); Retaskable to 5.1
DisplayPort	As Supported by GPU
HDMI	As Supported by GPU
DVI	As Supported by GPU
VirtualLink	As Supported by GPU
VGA Port	As Supported by GPU
Serial Port	Optional 1x Rear Port
Ethernet	2 x 1GbE - RJ45
PS/2	2 x PS/2
IEEE 1394	Not Available
eSATA	Optional PCIe Bracket
Parallel Port	Not Available
Optional USB Adapter	Dual Type-C Ports USB 3.1 Gen 1 Dual Type-A Ports USB 2.0
Optional Network Adapter	Intel I210-T1 Single Port Gigabit Ethernet Adapter Intel I350-T2 Dual Port Gigabit Ethernet Adapter Intel I350-T4 Quad Port Gigabit Ethernet Adapter PCI-E 1 x WiFi Card With BT HP External Antenna Kit (8265 AC)

Ethernet

Vendor	Intel Jacksonville I219LM, Intel Springville I210AT
Speeds	10/100/1000Mbps
Functions	PXE, ASF, WOL, Jumbo Frames, Teaming
Connectors	2 x RJ45

Audio

Vendor	Realtek
Type	HD (5.1)
Internal Speaker	Yes
Connectors	3 x Rear 3.5mm Jacks (Line In, Line Out, Microphone In)
Chipset	ALC662
Number of Channels	6 Channels
Number of Bits/Audio Resolution	6 Channel DAC Supports 16/20/24 bit PCM Stereo ADC Supports 16/20 bit PCM

Thermal

Temp Sensors	Ambient Thermal Sensor - Thermal Diode Connected to Super I/O CPU VR Sensor - Thermal Diode Connected to Super I/O DIMM VR Sensor- Thermal Diode Connected to Super I/O PSU Thermal Sensor- Thermistor PCI Zone 1 Sensor- Thermistor PCI Zone 1 Sensor- Thermistor PCI Zone 1 Sensor- Thermistor M.2 Sensor- Thermistor
Fans	2 x CPU Fan 4-pin Header With 3-pin Key Rear System Fan 4-pin Header 2 x Front Fan 4-pin Header 2 x ODD Bay Fan 4-pin Header With 3-pin Key PSU Fan Main PSU Power Connector

Power Specifications

Power Supply	1400W (Part Number: SP50H29490)	1400W (Part Number: SP50H29608) PSU-OCP/OVP updated
Power Efficiency	92% Efficient @ 50% Load	92% Efficient @ 50% Load
Main	C14	C14
Operating Voltage Range	100 - 240V	100 - 240V
Rated Voltage Range	90-264VAC	90-264VAC
Rated Line Frequency	47Hz / 63Hz	47Hz / 63Hz

Operating Line Frequency Range	50Hz / 60Hz	50Hz / 60Hz
Rated Input Current	9A-15A	9A-15A
Graphics	3 x 8 pin (6+2) 1 x 6 pin	3 x 8 pin (6+2) 1 x 6 pin
Power Supply Fan	Yes	Yes
ENERGY STAR® Qualified (config dependent)	Yes	Yes
80 PLUS Compliant	Yes	Yes
Built-in Self Test (BIST) LED	Yes	Yes
Aux Power Drop	Yes 3 x 8-pin (6+2) 1 x 6-pin	Yes 3 x 8-pin (6+2) 1 x 6-pin
Disclaimers	Power Output Limited to 1125W for 100-110V Input Voltage	Power Output Limited to 1125W for 100-110V Input Voltage

BIOS

Vendor	AMI
--------	-----

Chassis Information

Color	Graphite Black
PSU	One Fixed 1400W, Autosensing, 92% PSU, 80 PLUS Platinum Qualified
Thermal Solutions	Three System Fans Standard (2 front, 1 rear), One Fan per CPU, Two PSU Fans
Dimensions	200mm/7.87" W x 620mm/24.4" D x 446mm/17.56" H (with feet)
Weight	37kg / 81.6lbs

Packaging Dimensions

Height (mm/in)	626mm / 24.65"
Width (mm/in)	337mm / 13.27"
Depth (mm)	798mm / 31.42"
Weight (kgs/lbs)	37kg / 81.6lbs

Security & Serviceability

TPM	Infineon SLB9665TT TPM 2.0
-----	----------------------------

Asset ID	Yes, 1024 x 8bit
vPro	Intel vPro for WS (AMT 9.x)
Cable Lock Support	Yes, Optional Kensington Cable Lock
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes
Power-On Password	Yes
Setup Password	Yes
NIC LEDs (integrated)	Yes
Access Panel Key Lock	Unique Key Lock Kit - Optional Common Key Lock Kit - Optional
Boot Sequence Control	Yes
Padlock Support	Not Supported
Boot Without Keyboard and/or Mouse	Yes
Access Panel	Tool-less Side Cover Removal
Optical Drive	Tool-less
Hard Drives	Tool-less
Expansion Cards	Tool-less
Processor Socket	Tool-less
Color Coded User Touch Points	Yes
Color-coordinated Cables and Connectors	Yes
Memory	Tool-less
System Board	Tool-less
Restore CD/DVD/USB Set	Not Included, Restore Media Available via Lenovo Customer Support Center

Operating Environment

Air Temperature	Operating: 10°C to 35°C (50°F to 95°F)
Storage	Storage: -40°C to 60°C (-40°F to 140°F) in Original Shipping Carton Storage: -10°C to 60°C (14°F to 140°F) Without Carton
Humidity	Relative Humidity Operating: 10% to 80% (non-condensing) Relative Humidity Storage/Transit: 10% to 90% (non-condensing) Wet Bulb Temperature Operating: 25°C (77°F) max Wet Bulb Temperature Non-operating: 40°C (104°F) max
Altitude	Operating: -15.2m to 3048m (-50ft to 10000ft) Storage: -15.2m to 10668m (-50ft to 35000ft)
Vibration	Package Vibration: Random, 1.04G at 2-200 Hz, 15 Minutes XYZ 6 faces Operating Vibration: Random, 0.27G at 5-500 Hz, 30 Minutes Per Surface (X,Y,Z) Non-Operating Vibration: Random, 1.04G at 2-200 Hz, 15 Minutes Per Surface (±X, ±Y, ±Z)
Shock	Operation Shock: 3ms (15G) for 4 Axis (+X, -X, +Y, -Y)

	<p>3ms (30G) for 2 Axis (+Z, -Z), Half-sine Wave, Each Side Will do One Time</p> <p>Rack Operation Shock: 5ms (15G) for 6 Axis (+X, -X, +Y,-Y,+Z, -Z), Half-sine Wave, Each Side Will do One Time</p> <p>Non-operating Shock: Trapezoidal Wave, 50G, 9ms, 6 Sides (+X, -X, +Y,-Y, +Z ,-Z), Filter 300Hz, Each Side Shock One Time</p>
--	---

SECTION II: Platform Detail

Board Size	14.06" x 14.76" (357mm x 375mm)
Layout	Custom ATX

Motherboard Core

Processor Support	Xeon Scalable Processors (Platinum, Gold, Silver, Bronze)
Socket Type	Socket-P0 (LGA 3647)
Memory Support	DDR4 up to 2933MHz RDIMM / LRDIMM Memory
CPU-CPU Interconnect	UPI up to 10.4GT/s
Voltage Regulator	Intel VR13.0 - 240W TDP Capable
Chipset (PCH)	Intel C621
Flash	32MB
Super I/O	Nuvoton NCT6685
Clock	Intel Native isCLK
Audio	Realtek ALC662 Codec
Ethernet	Intel Jacksonville I219LM, Intel Springville I210AT
SAS	Optional via Broadcom Adapter
Disclaimers	Optional via Broadcom Adapter

Supported Components

Processor Level	Platinum	Gold	Silver	Bronze
Processor	Intel Xeon PLATINUM 8280 Intel Xeon PLATINUM 8160T	Intel Xeon GOLD 6254 Intel Xeon GOLD 6246 Intel Xeon GOLD 6244 Intel Xeon GOLD 6242 Intel Xeon GOLD 6238T Intel Xeon	Intel Xeon SILVER 4216 Intel Xeon SILVER 4215 Intel Xeon SILVER 4214 Intel Xeon SILVER 4214R Intel Xeon SILVER 4210 Intel Xeon	Intel Xeon BRONZE 3204

	GOLD 6234 Intel Xeon GOLD 6230 Intel Xeon GOLD 6226 Intel Xeon GOLD 5222 Intel Xeon GOLD 5218 Intel Xeon GOLD 6154 Intel Xeon GOLD 6142 Intel Xeon GOLD 6136 Intel Xeon GOLD 6134 Intel Xeon GOLD 6128 Intel Xeon GOLD 5122 Intel Xeon GOLD 5120T Intel Xeon GOLD 5118	SILVER 4210R Intel Xeon SILVER 4209T Intel Xeon SILVER 4208 Intel Xeon SILVER 4116 Intel Xeon SILVER 4114 Intel Xeon SILVER 4114T Intel Xeon SILVER 4112 Intel Xeon SILVER 4110 Intel Xeon SILVER 4109T Intel Xeon SILVER 4108	
Memory Type	RDIMMs - 2666MHz or 2933MHz, CPU Dependent	LRDIMMs - 2666MHz	
Memory	8GB DDR4 ECC RDIMM PC4-2933 16GB DDR4 ECC RDIMM PC4-2933 32GB DDR4 ECC RDIMM PC4-2933 64GB DDR4 ECC RDIMM PC4-2933 8GB DDR4 ECC RDIMM PC4-2666 16GB DDR4 ECC RDIMM PC4-2666 32GB DDR4 ECC RDIMM PC4-2666	64GB DDR4 ECC LRDIMM PC4-2666	

Storage

3.5" SATA Hard Disk Drive (HDD)	1TB SATA - 7200rpm, 6Gb/s, 3.5" 2TB SATA - 7200rpm, 6Gb/s, 3.5" 4TB SATA - 7200rpm, 6Gb/s, 3.5" (enterprise class) 6TB SATA - 7200rpm, 6Gb/s, 3.5" (enterprise class)
2.5" SATA Hard Disk Drive (HDD)	500GB 2.5" SATA HDD 7200rpm (FIPS certified)
2.5" SATA Solid State Drive (SSD)	256GB SATA - SSD, 6Gb/s, TLC, 2.5", OPAL 512GB SATA - SSD, 6Gb/s, TLC, 2.5" OPAL 512GB SATA - SSD, 6Gb/s, TLC, 2.5", Non-OPAL 1024GB SATA - SSD, 6Gb/s, TLC, 2.5" OPAL 2048GB SATA - SSD, 6Gb/s, TLC, 2.5" OPAL
M.2 PCIe Solid State Drive (SSD)	256GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL 256GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL - Intel 512GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL 512GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL - Intel 512GB M.2 PCIe - SSD, Gen 3 x4, NVMe, Non-OPAL 1024GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL 2048GB M.2 PCIe - SSD, Gen 3 x4, NVMe, OPAL
PCIe Add-in-Card Solid State Drive (SSD)	480GB Half Height, Half Length, PCIe NVMe SSD, Gen 3 x4 - Intel 905p

RAID

RAID Requirements	M.2 RAID via Intel VROC SATA RAID via Onboard Intel Controller or Broadcom Adapter SAS RAID via Broadcom Adapter
Notes	Supported RAID levels for a system will vary from the stated capabilities of the RAID controller due to dependencies on the number and capacity of physical disks in the system and on customer requirements for performance, fault tolerance, or data redundancy. Max supported RAID 0/1/5/10.
Optional Hard Disk Drive Controllers	Broadcom 9460-16i ROC PCIe Adapter, Supports 0/1/5/10 Broadcom 9440-8i IOC PCIe Adapter, Supports 0/1/5/10
Intel VROC	Intel Virtual RAID On CPU (VROC) - Basic, Supports 0/1/10 Intel Virtual RAID On CPU (VROC) - Premium, Supports 0/1/5/10

Optical Drive/Removable Media

DVD-ROM Drive	DVD-ROM Drive - 16x/48x Slim SATA DVD-ROM
DVD Burner/CD-RW Drive	DVD Burner/CD-RW Rambo Drive Slim ODD DVD Burner/CD-RW
Blu-Ray Burner Drive	Blu-Ray Burner Drive w/AACS encryption Slim Blu-Ray ODD DVD Burner
Media Card Reader Specifications	Front 9-in-1 USB 2.0 Media Card Reader Standard Optional Front 15-in-1 Media Card Reader (requires Flex module)

Keyboard and Pointing Devices

Keyboard	Traditional USB Keyboard Traditional PS/2 Keyboard Smart Card USB Keyboard Calliope USB Keyboard
Pointing Devices	Calliope USB Mouse Lenovo USB Laser Mouse Fingerprint USB Mouse PS/2 Optical Mouse

Expansion Bays

5.25" External Access Bays	Three 5.25" Flex Bays, Supports the Following: <ul style="list-style-type: none"> • Up to Three Half Height Optical Drives • Up to Two 5.25" Slim ODD Cages, Each Supports One 9.0mm Optical Drive • Up to One 5.25" Slim ODD and HDD Cage for One 9.0mm Optical Drive Plus One 3.5" or 2.5" SATA Disk • Up to One Front Access Storage Enclosure for One 3.5" or 2.5" SATA Disk • Up to One Flex Module for One or More of the Following Options: 9.0mm Optical/15-in-1 USB 3.1 Gen 1 Reader/Front eSATA/Front Thunderbolt/Front USB 3.1 Gen 1 Type-C • Up to Three Front Removable Drive Enclosure, Supports One M.2 SSD
----------------------------	--

	<p>Each, Each Front Removable Drive Enclosure Comes with a PCIe x4 Adapter</p> <p>Note: 1. Only one can be supported from the following: 15-in-1 memory card reader, dual Thunderbolt ports</p> <p>Note: 2. Up to two ports are supported from 1394, eSATA, and USB Type-C</p>
--	--

PCIe Adapters

Network	<p>Intel I210-T1 Single Port Gigabit Ethernet Adapter</p> <p>Intel I350-T2 Dual Port Gigabit Ethernet Adapter</p> <p>Intel I350-T4 Quad Port Gigabit Ethernet Adapter</p> <p>Bitland BN8E88 1000M PCIE ASF FH</p> <p>Aquantia 5G Ethernet Adapter (single port)</p> <p>Intel X540-T2 10G Ethernet Adapter (dual port)</p> <p>Intel X550-T2 10G Ethernet Adapter (dual port)</p>
Thunderbolt	<p>Front Thunderbolt Card Kit Supports Two Optional Thunderbolt 3 Ports (USB Type-C) on Flex module, One of Two Ports Supports Video Out</p> <p>Rear Thunderbolt PCIe Adapter</p>
USB	<p>Rear USB 3.1 Type-C Gen 1 PCIe Adapter V1.0 FH Bracket</p>
WiFi Cards	<p>Intel PCIe WiFi Card With BT External Antenna Kit (8265 AC)</p>
PCIe to M.2 Adapter Card	<p>PCIe x4 to M.2 Adapter (for NVMe SSD)</p> <p>Quad M.2 PCIe Adapter</p>

SECTION III: Supported Component Detail

CPU Specifications

CPU	Intel Xeon PLATINUM 8280	Intel Xeon PLATINUM 8160T	Intel Xeon GOLD 6254	Intel Xeon GOLD 6154	Intel Xeon GOLD 6242
# of Cores	28	24	18	18	16
# of Threads	56	48	36	36	32
Processor Base Frequency	2.7GHz	2.1GHz	3.1GHz	3GHz	2.8GHz
Max Turbo Frequency	4GHz	3.7GHz	4GHz	3.7GHz	3.9GHz
Cache	38.5MB	33MB L3	24.75MB	24.75MB L3	22MB
TDP	205W	150W	200W	200W	150W
Intel ARK Spec Link	Intel Xeon PLATINUM 8280	Intel Xeon PLATINUM 8160T	Intel Xeon GOLD 6254	Intel Xeon GOLD 6154	Intel Xeon GOLD 6242

CPU Specifications

CPU	Intel Xeon GOLD 6142	Intel Xeon GOLD 6136	Intel Xeon GOLD 6238T	Intel Xeon GOLD 6234	Intel Xeon GOLD 6134
# of Cores	16	12	22	8	8
# of Threads	32	24	44	16	16
Processor Base Frequency	2.6GHz	3GHz	1.9GHz	3.3GHz	3.2GHz
Max Turbo Frequency	3.7GHz	3.7GHz	3.7GHz	4GHz	3.7GHz
Cache	22MB L3	24.75MB L3	30.25MB	24.75MB	24.75MB L3
TDP	150W	150W	125W	130W	130W
Intel ARK Spec Link	Intel Xeon GOLD 6142	Intel Xeon GOLD 6136	Intel Xeon GOLD 6238T	Intel Xeon GOLD 6234	Intel Xeon GOLD 6134

CPU Specifications

CPU	Intel Xeon GOLD 6230	Intel Xeon GOLD 6128	Intel Xeon GOLD 5222	Intel Xeon GOLD 5122	Intel Xeon GOLD 5120T
# of Cores	20	6	4	4	14
# of Threads	40	12	8	8	28
Processor Base Frequency	2.1GHz	3.4GHz	3.8GHz	3.6GHz	2.2GHz
Max Turbo Frequency	3.9GHz	3.7GHz	3.9GHz	3.7GHz	3.2GHz
Cache	27.5MB	19.25MB L3	16.5MB	16.5MB L3	19.25MB L3
TDP	125W	115W	105W	105W	105W
Intel ARK Spec Link	Intel Xeon GOLD 6230	Intel Xeon GOLD 6128	Intel Xeon GOLD 5222	Intel Xeon GOLD 5122	Intel Xeon GOLD 5120T

CPU Specifications

CPU	Intel Xeon GOLD 5218	Intel Xeon GOLD 5118	Intel Xeon GOLD 5115	Intel Xeon SILVER 4216	Intel Xeon SILVER 4116
# of Cores	16	12	10	16	12
# of Threads	32	24	20	32	24
Processor Base Frequency	2.3GHz	2.3GHz	2.4GHz	2.1GHz	2.1GHz
Max Turbo Frequency	3.9GHz	3.2GHz	3.2GHz	3.2GHz	3GHz
Cache	22MB	16.5MB L3	13.75MB L3	22MB	16.5MB L3
TDP	125W	105W	85W	100W	85W
Intel ARK Spec Link	Intel Xeon GOLD 5218	Intel Xeon GOLD 5118	Intel Xeon GOLD 5115	Intel Xeon SILVER 4216	Intel Xeon SILVER 4116

CPU Specifications

CPU	Intel Xeon SILVER 4215	Intel SILVER 4214	Intel Xeon SILVER 4114	Intel Xeon SILVER 4114T	Intel Xeon SILVER 4112
# of Cores	8	12	10	10	4
# of Threads	16	24	20	20	8
Processor Base Frequency	2.5GHz	2.2GHz	2.2GHz	2.2GHz	2.6GHz
Max Turbo Frequency	3.5GHz	3.2GHz	3GHz	3GHz	3GHz
Cache	11MB	16.5MB	13.75MB L3	13.75MB L3	8.25MB L3
TDP	85W	85W	85W	85W	85W
Intel ARK Spec Link	Intel Xeon SILVER 4215	Intel SILVER 4214	Intel Xeon SILVER 4114	Intel Xeon SILVER 4114T	Intel Xeon SILVER 4112

CPU Specifications

CPU	Intel Xeon SILVER 4210	Intel Xeon SILVER 4110	Intel Xeon SILVER 4209T	Intel Xeon SILVER 4109T	Intel Xeon SILVER 4208
# of Cores	10	8	8	8	8
# of Threads	20	16	16	16	16
Processor Base Frequency	2.2GHz	2.1GHz	2.2GHz	2GHz	2.1GHz
Max Turbo Frequency	3.2GHz	3GHz	3.2GHz	3GHz	3.2GHz
Cache	13.75MB	11MB L3	11MB	11MB L3	11MB
TDP	85W	85W	70W	70W	85W
Intel ARK Spec Link	Intel Xeon SILVER 4210	Intel Xeon SILVER 4110	Intel Xeon SILVER 4209T	Intel Xeon SILVER 4109T	Intel Xeon SILVER 4208

CPU Specifications

CPU	Intel Xeon SILVER 4108	Intel Xeon BRONZE 3204	Intel Xeon BRONZE 3104
# of Cores	8	6	6
# of Threads	16	6	6
Processor Base Frequency	1.8GHz	1.9GHz	1.7GHz
Max Turbo Frequency	3GHz	Not Available	Not Available
Cache	11MB L3	8.25MB	8.25MB L3
TDP	85W	85W	85W
Intel ARK Spec Link	Intel Xeon SILVER 4108	Intel Xeon BRONZE 3204	Intel Xeon BRONZE 3104

HDD Specifications

Drive	500GB SATA - 7200rpm, 6Gb/s, 2.5"	1TB SATA - 7200rpm, 6Gb/s, 3.5"	2TB SATA - 7200rpm, 6Gb/s, 3.5"	4TB SATA - 7200rpm, 6Gb/s, 3.5"	6TB SATA - 7200rpm, 6Gb/s, 3.5"
3.5" SATA Hard Disk Drive (HDD)	Not Available	Yes	Yes	Yes	Yes
2.5" SATA Hard Disk Drive (HDD)	Yes	Not Available	Not Available	Not Available	Not Available
Connector	SATA	SATA	SATA	SATA	SATA
Transfer Rate (Gb/sec)	160MB/s OD read	Average data rate, read/write 156MB/s	Average data rate, read/write 156MB/s	Sustained data transfer rate 216 - 226MB/s	Sustained data transfer rate 216 - 226MB/s
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200
DC Power to Drive Ready (sec)	3.5	<10.0	<17.0	<17.0	<17.0
Average Latency (msec)	4.2	4.16	4.16	4.16	4.16
Input (VDC)	5	5	5	5	5
Typical (Watts)	1.9	6.19	6.7	7.35	8.13
Idle (Watts)	0.7	4.6	4.5	5.45	6.21
Physical Dimensions	69.85mm x 100.34mm x 7mm	101.6mm x 146.99mm x 19.88mm	101.6mm x 146.99mm x 26.1mm	101.85mm x 147mm x 26.1mm	101.85mm x 147mm x 26.1mm
Weight (grams)	90	420	535	680	705
Operating (C) Ambient	0 to 60	0 to 60	0 to 60	5 to 60	5 to 60
Operating (C) Base Casting	60	60	60	60	60
Non-Operating (C) Ambient	(-40 to 70)	(-40 to 70)	(-40 to 70)	(-40 to 70)	(-40 to 70)
Gradient (C per Hour)	20	20	20	20	20
Operating (Gs @ 2ms)	400	70	80	Read 70 Gs / Write 40 Gs	Read 70 Gs / Write 40 Gs
Non-Operating (Gs @ 2ms)	1000	350	300	300	250

Solid State Storage Specifications

Drive	256GB 2.5" SATA SSD	512GB 2.5" SATA SSD	1TB 2.5" SATA SSD	2TB 2.5" SATA SSD	256GB NVMe M.2 SSD TLC
Dimensions Millimeters (W x D x H)	70 x 100 x 7.0	70 x 100 x 7.0	70 x 100 x 7.0	70 x 100 x 7.0	22 x 80 x 2.3
Interface Type	SATA-III	SATA-III	SATA-III	SATA-III	PCIe Gen 3.0 x4 NVMe
Power Active (AVG)	1.8W	1.9W	2.2W	6W	5W
Power Idle	50mW	50mW	50mW	50mW	50mW
Typical Sequential Read	540MB/s	540MB/s	540MB/s	530MB/s	3000MB/s

Typical Sequential Write	500MB/s	500MB/s	500MB/s	500MB/s	1300MB/s
Operating Temperature Range	0 to 55°C	0 to 55°C	0 to 55°C	0 to 55°C	0 to 55°C
Endurance Rating (Lifetime Writes)	85TB	150TB	300TB	600TB	85TB
Mean Time Between Failures (MTBF)	2.0M POH	2.0M POH	2.0M POH	2.0M POH	2.0M POH
Hardware Encryption	AES 256 bit	AES 256 bit	AES 256 bit	AES 256 bit	AES 256 bit
Disclaimers	SSD performance measured with Crystal Disk Mark version 6.0.2 with the default 1000 MB data set. Sequential measurements are with 1 Thread, Queue-Depth 32. Random measurements are with 4 threads and queue-depth 32.				

Solid State Storage Specifications

Drive	512GB NVMe M.2 SSD TLC	1024GB NVMe M.2 SSD TLC	2048GB NVMe M.2 SSD TLC	480GB AIC Optane™ SSD	1.5TB U.2 Optane™ SSD
Dimensions Millimeters (W x D x H)	22 x 80 x 2.3	22 x 80 x 2.3	22 x 80 x 2.3	20 x 168 x 104	70 x 100 x 15
Interface Type	PCIe Gen 3.0 x4 NVMe	PCIe Gen 3.0 x4 NVMe	PCIe Gen 3.0 x4 NVMe	PCIe Gen 3.0 x4 NVMe	PCIe Gen 3.0 x4 NVMe
Power Active (AVG)	5W	5W	5W	18W	18W
Power Idle	50mW	50mW	50mW	7W	7W
Typical Sequential Read	3200MB/s	3200MB/s	3500MB/s	2700MB/s	2700MB/s
Typical Sequential Write	1600MB/s	1600MB/s	3000MB/s	2200MB/s	2200MB/s
Typical Random Read (4GB Span)	340K IOPS	340K IOPS	600K IOPS	575K IOPS	575K IOPS
Typical Random Write (4GB Span)	275K IOPS.	275K IOPS.	500K IOPS.	550K IOPS	550K IOPS
Operating Temperature Range	0 to 55°C	0 to 55°C	0 to 55°C	0 to 85°C	0 to 85°C
Endurance Rating (Lifetime Writes)	150TB	300TB	600TB	8.76PB	27.3PB
Mean Time Between Failures (MTBF)	2.0M POH	2.0M POH	2.0M POH	2.0M POH	2.0M POH
Hardware Encryption	AES 256 bit	AES 256 bit	AES 256 bit	No	No

HDD Controllers

PCI Bus	PCH Integrated
PCI Modes	SATA 3.0
RAID Levels	0/1/5/10
Data Transfer Rates	6Gb/s
Internal Connectors	2 x MiniSAS HD (2 ports each) + 3 x SATA

Optical Drive Specifications

Operating Systems Supported	Windows 10 Pro for Workstations (Preload) Windows 7 Pro 64 Red Hat Enterprise Linux 7.3 Ubuntu 16.04 and 18.04.2
Temperature	10° - 35°C (50° - 95°F)
Relative Humidity	10%-80% (non-condensing)
Maximum Wet Bulb Temperature	25°C max

Discrete Graphics Adapter

Adapter	NVIDIA NVS 810	Quadro P400	Quadro P600	Quadro P620	Quadro P1000
Bus Interface	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16
Display Interface	8 x mDP 1.2	3 x mDP 1.4	4 x mDP 1.4	4 x mDP 1.4	4 x mDP 1.4
Graphics Chipset	Maxwell	Pascal	Pascal	Pascal	Pascal
Memory Clock Frequency (MHz)	900MHz	1003MHz	1002MHz	1252MHz	1253MHz
Memory Size	4GB DDR3 (2GB per GPU)	2GB GDDR5	2GB GDDR5	2GB GDDR5	4GB GDDR5
Memory Interface	128-bit (64-bit per GPU)	64-bit	128-bit	128-bit	128-bit
Memory Bandwidth	28.8GB/s	Up to 32GB/s	Up to 64GB/s	Up to 80GB/s	Up to 82GB/s
GPU Cores	CUDA Cores: 1024 (512 cores per GPU)	CUDA Cores: 256	CUDA Cores: 384	CUDA Cores: 512	CUDA Cores: 640
GPU Core Frequency (MHz)	1033MHz	1228MHz	1329MHz	1266MHz	1266MHz
Maximum Power Consumption	68W	30W	40W	40W	47W
Supported Resolutions and Max Refresh Rates (Hz) (Note: Analog and/or Digital)	8 x 4096x2160 @ 30Hz 4 x 4096x2160 @ 60Hz	3 x 4096x2160 @ 60Hz 1 x 5120x2880 @ 60Hz	4 x 4096x2160 @ 60Hz 4 x 5120x2880 @ 60Hz	4 x 4096x2160 @ 60Hz 4 x 5120x2880 @ 60Hz	4 x 4096x2160 @ 60Hz 4 x 5120x2880 @ 60Hz
Thermal Solution	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink
Dimension	4.4" H x 7.8" L Single Slot	2.713" H x 5.7" L Single Slot, Low Profile	2.713" H x 5.7" L Single Slot, Low Profile	2.713" H x 5.7" L Single Slot, Low Profile	2.713" H x 5.7" L Single Slot, Low Profile
Advanced Display	Not	Not	Not	Not	Not

	Available	Available	Available	Available	Available
SLI/NVLink Support	Not Available	Not Available	Not Available	Not Available	Not Available

Discrete Graphics Adapter

Adapter	Quadro P2000	Quadro P2200	Quadro P4000	Quadro P5000	Quadro P6000
Bus Interface	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16
Display Interface	4 x DP 1.4	4 x DP 1.4	4 x DP 1.4	4 x DP 1.4 1 x DVI-D DL	4 x DP 1.4 1 x DVI-D DL
Graphics Chipset	Pascal	Pascal	Pascal	Pascal	Pascal
Memory Clock Frequency (MHz)	1752MHz	1251MHz	1901MHz	1127MHz	1127MHz
Memory Size	5GB GDDR5	5GB GDDR5X	8GB GDDR5	16GB GDDR5X	24GB GDDR5X
Memory Interface	160-bit	160-bit	256-bit	256-bit	384-bit
Memory Bandwidth	Up to 140GB/s	Up to 200GB/s	Up to 243GB/s	Up to 288GB/s	Up to 432GB/s
GPU Cores	CUDA Cores: 1024	CUDA Cores: 1280	CUDA Cores: 1792	CUDA Cores: 2560	CUDA Cores: 3840
GPU Core Frequency (MHz)	1076MHz	1000MHz	1202MHz	1607MHz	1645MHz
Maximum Power Consumption	75W	75W	105W	180W	250W
Supported Resolutions and Max Refresh Rates (Hz) (Note: Analog and/or Digital)	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz	7680 x 4320 @ 30Hz (Max DP 1.4) 2560 x 1600 @ 60Hz (Max DVI-D DL)	7680 x 4320 @ 30Hz (Max DP 1.4) 2560 x 1600 @ 60Hz (Max DVI-D DL)
Thermal Solution	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink
Dimension	4.4" H x 7.9" L Single Slot	4.4" H x 7.9" L Single Slot	4.4" H x 9.5" L Single Slot, Full Height	4.4" H x 10.5" L Dual Slot, Full Height	4.4" H x 10.5" L Dual Slot, Full Height
Advanced Display	Not Available	Not Available	SYNC 2	SYNC 2	SYNC 2
SLI/NVLink Support	Not Available	Not Available	Not Available	SLI	SLI

Discrete Graphics Adapter

Adapter	Quadro RTX 4000	Quadro RTX 5000	Quadro RTX 6000	Quadro RTX 8000	Quadro GP100
Bus Interface	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16	PCIe 3.0 x16

Display Interface	3 x DP 1.4 1 x VirtualLink	4 x DP 1.4 1 x VirtualLink	4 x DP 1.4 1 x VirtualLink	4 x DP 1.4 1 x VirtualLink	4 x DP 1.4 1 x DVI-D DL
Graphics Chipset	Turing	Turing	Turing	Turing	Pascal
Memory Clock Frequency (MHz)	1625MHz	1750MHz	1750MHz	1750MHz	715MHz
Memory Size	8GB GDDR6	16GB GDDR6	24GB GDDR6	48GB GDDR6	16GB HBM2
Memory Interface	256-bit	256-bit	384-bit	384-bit	4096-bit
Memory Bandwidth	Up to 416GB/s	Up to 448GB/s	Up to 672GB/s	Up to 672GB/s	Up to 717GB/s
GPU Cores	CUDA Cores: 2304 Tensor Cores: 288 RT Cores: 36	CUDA Cores: 3072 Tensor Cores: 384 RT Cores: 48	CUDA Cores: 4608 Tensor Cores: 576 RT Cores: 72	CUDA Cores: 4608 Tensor Cores: 576 RT Cores: 72	CUDA Cores: 3584
GPU Core Frequency (MHz)	1005MHz	1620MHz	1440MHz	1395MHz	1204MHz
Maximum Power Consumption	Total board power: 160W Total graphics power: 125W	Total board power: 265W Total graphics power: 230W	Total board power: 295W Total graphics power: 260W	Total board power: 295W Total graphics power: 260W	235W
Supported Resolutions and Max Refresh Rates (Hz) (Note: Analog and/or Digital)	4 x 3840x2160 @ 120Hz 4 x 5120x2880 @ 60Hz 4 x 7680x4320 @ 60Hz	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz 2 x 7680x4320 @ 60Hz	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz 2 x 7680x4320 @ 60Hz	4 x 3840 x 2160 @ 120Hz 4 x 5120x2880 @ 60Hz 2 x 7680x4320 @ 60Hz	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz
Thermal Solution	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink	Ultra-quiet Active Fansink
Dimension	4.4" H x 9.5" L Single Slot	4.4" H x 10.5" L Dual Slot, Full Height	4.4" H x 10.5" L Dual Slot, Full Height	4.4" H x 10.5" L Dual Slot, Full Height	4.4" H x 10.5" L Dual Slot, Full Height
Advanced Display	SYNC 2	SYNC 2	SYNC 2	SYNC 2	Not Available
SLI/NVLink Support	Not Available	NVLink	NVLink	NVLink	NVLink

Discrete Graphics Adapter

Adapter	Quadro GV100
Bus Interface	PCIe 3.0 x16
Display Interface	4 x DP 1.4
Graphics Chipset	Volta
Memory Clock Frequency (MHz)	858MHz

Memory Size	32GB HBM2
Memory Interface	4096-bit
Memory Bandwidth	Up to 870GB/s
GPU Cores	CUDA Cores: 5120 Tensor Cores: 640
GPU Core Frequency (MHz)	1132MHz
Maximum Power Consumption	250W
Supported Resolutions and Max Refresh Rates (Hz) (Note: Analog and/or Digital)	4 x 4096x2160 @ 120Hz 4 x 5120x2880 @ 60Hz 2 x 7680x4320 @ 60Hz
Thermal Solution	Ultra-quiet Active Fansink
Dimension	4.4" H x 10.5" L Dual Slot, Full Height
Advanced Display	Not Available
SLI/NVLink Support	NVLink

Intel® Ethernet Specifications

Card	Intel I210-T1 Single Port Gigabit Ethernet Adapter (Springville)	Intel I350-T2 Dual Port Gigabit Ethernet Adapter (Stony Lake T2)	Intel I350-T4 Quad Port Gigabit Ethernet Adapter (Stony Lake T4)	Intel X540-T2 Dual Port Copper 10Gb Ethernet Adapter	Intel X710-DA2 Dual Port Fiber 10Gb Ethernet Adapter
Supplier PN	I210T1, MM# 941033	I350T2G1P20, MM# 928941	I350T4G1P20, MM# 928942	MM#928955	MM# 952103
Data Rates Supported	10/100/1000 Mbps copper	10/100/1000 Mbps (Copper), 1000Mbps (Fiber)	10/100/1000 Mbps (Copper), 1000Mbps (Fiber)	100/1000Mbps and 10Gbps Copper	1GbE/10GbE Optical fiber 10GbE Direct Attach (DAC)
Controller Details	Intel® Ethernet Controller I210	Intel Ethernet Controller I350	Intel Ethernet Controller I351	Intel Ethernet Controller X540	Intel Ethernet Controller X710-AM2
Controller Bus Architecture	PCIe 2.1 (5GT/s)	PCIe 2.1 (5GT/s)	PCIe 2.1 (5GT/s)	PCIe 2.1 (5GT/s)	PCIe 3.0 (8GT/s)
Data Transfer Mode	Ethernet	Ethernet	Ethernet	Ethernet	Ethernet
Power Consumption	0.81W	Copper: I350-T2 V2= 4.4W Fiber: I350-F2= 5.5W	Copper: I350T4V2= 5W LC-Fiber: I350F4= 6W	X540-T2: 10Gps= 17.4W 1Gbps= 9.5W 100Mbps=6.6W X540-T1: 10Gbps=10.8W 1Gbps= 7.7W 100Mbps= 6.4W	Dual-port 10GBASE-SR= 4.3W typ/4.8W max Dual-port 1000BASE-SX= 4W typ/4.3W max Dual-port 10GBASE-LR= 4.5W

					typ/ 5.1W max Dual-port Direct Attach (Twinax)= 3.3W typ/3.7W max
IEEE Standards Compliance	IEEE 802.3/10BASE-T, 100BASE-TX, 1000BASE-T	IEEE 802.3/10BASE-T, 100BASE-TX, 1000BASE-T	IEEE 802.3/10BASE-T, 100BASE-TX, 1000BASE-T	IEEE 802.3 100/1000/10GBASE-T	IEEE 802.3 1/10/10GBASE-SR/LR, SFF-8431 10GSFP+DAC
Boot ROM Support	PXE boot, Intel iSCSI Remote Boot for Windows, Linux and Vmware, Intel BootAgent Software via PXE or BootP, WDMS or UEFI	PXE boot, Intel iSCSI Remote Boot for Windows, Linux and Vmware, Intel BootAgent Software via PXE or BootP, WDMS or UEFI	PXE boot, Intel iSCSI Remote Boot for Windows, Linux and Vmware, Intel BootAgent Software via PXE or BootP, WDMS or UEFI	PXE boot, Intel iSCSI Remote Boot for Windows, Linux and Vmware, Intel BootAgent Software via PXE or BootP, WDMS or UEFI	PXE boot, Intel iSCSI Remote Boot for Windows, Linux and Vmware, Intel BootAgent Software via PXE or BootP, WDMS or UEFI
Network Transfer Mode (Full/Half Duplex)	Supported	Supported	Supported	Supported	Supported
Network Transfer Rate	1,000Mbps Full Duplex	1,000Mbps Full Duplex	1,000Mbps Full Duplex	1,000Mbps Full Duplex	1,000Mbps Full Duplex
Operating System Driver Support	Windows 7/8/10, Linux, Free BSD, XEN,Vmware	Windows 7/8/10, Linux, Free BSD, XEN,Vmware	Windows 7/8/10, Linux, Free BSD, XEN,Vmware	Windows 7/8/10, Windows ServerLinux, FreeBSD	Windows 2008, 2012; RHEL 6.5/7.0, FreeBSD 9/10, Vmware ESXi 5.x
Manageability	Supported	Supported	Supported	Supported	Supported
Manageability Capabilities Alerting	Supported	Supported	Supported	Supported	Supported
TDP	Firmware Based Thermal Management	Firmware Based Thermal Management	Firmware Based Thermal Management	Firmware Based Thermal Management	Not Available
Operating Temperature Range	0°C to 55°C (32°F to 131°F)	0°C to 55°C (32°F to 131°F)	0°C to 55°C (32°F to 131°F)	0°C to 55°C (32°F to 131°F)	0°C to 55°C (32°F to 131°F)
# of Ports	1	2	4	2	2
Data Rate Per Port	10/100/1000 Mbps (copper)	10/100/1000 Mbps (copper), 1000Mbps (fiber)	10/100/1000 Mbps (copper), 1000Mbps (fiber)	100/1,000Mbps, 10Gbps	1Gbps, 10Gbps
System Interface Type	PCIe Gen 2.1	PCIe Gen 2.1	PCIe Gen 2.1	PCIe Gen 2.1	PCIe 3.0
NC Sideband Interface	Not Available	Not Available	Not Available	Not Available	Yes
Jumbo Frames Supported	Yes	Yes	Yes	Yes	Yes

1000Base-T	Yes	Yes	Yes	Yes	Not Available
IEEE 1588	Supported	Supported	Supported	Not Available	Supported
Supported Under vPro	Not Available	Not Available	Not Available	Not Available	Not Available

Intel® Ethernet Specifications

Card	Intel Ethernet SFP+ SR Optics Module	Intel Dual Band Wireless-AC 7260 ASM	Intel Winstorm Peak 8265 2x2 AC+BT 4.2 Vpro M.2 Combo
Supplier PN	MM#: 941243	7260HMWDTX.R, MM# 936170	MM#: 946658
Data Rates Supported	Not Available	Intel Dual Band Wireless-AC 7260	Intel Dual Band Wireless-AC 8265
Controller Details	Not Available	Intel Dual Band Wireless-AC 7260, Dual Band, 2x2, WiFi+BT	Intel Dual Band Wireless-AC 8265, 2x2, WiFi+BT, MU-MIMO
Controller Bus Architecture	Not Available	PCIe M.2	PCIe M.2
Data Transfer Mode	Not Available	WiFi (802.11ac), 2.4GHz, 5GHz	WiFi (802.11ac), 2.4GHz, 5GHz
Power Consumption	Not Available	Not Available	Not Available
IEEE Standards Compliance	Not Available	IEEE 802.11abgn, 802.11ac, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w	IEEE 802.11abgn, 802.11ac, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w, 802.11r, 802.11k, 802.11v (pending)
Boot ROM Support	Not Available	Not Available	Not Available
Network Transfer Mode (Full/Half Duplex)	Not Available	Not Available	Not Available
Network Transfer Rate	Not Available	300/867Mbps	867Mbps
Operating System Driver Support	Not Available	Windows 10, 32-bit*, Windows 10, 64-bit*, Windows 8.1, 32-bit*, Windows 8.1, 64-bit*, Windows 8, 32-bit*, Windows 8, 64-bit*, Windows 7, 32-bit*, Windows 7, 64-bit*, Linux*	Windows 10, 64-bit*, Windows 8.1, 64-bit*, Windows 7, 32-bit*, Windows 7, 64-bit*, Linux*
Manageability	Not Available	Not Available	Not Available
Manageability Capabilities Alerting	Not Available	Not Available	Not Available
TDP	Not Available	Not Available	Not Available
Operating Temperature Range	Not Available	0°C to 80°C (32°F to 176°F)	0°C to 80°C (32°F to 176°F)
# of Ports	Not Available	Not Available	Not Available
Data Rate Per Port	Not Available	Not Available	Not Available

System Interface Type	Not Available	PCIe M.2	PCIe M.2
NC Sideband Interface	Not Available	Not Available	Not Available
Jumbo Frames Supported	Not Available	Not Available	Not Available
1000Base-T	Not Available	Not Available	Not Available
IEEE 1588	Not Available	Not Available	Not Available
Supported Under vPro	Not Available	Supported	Supported

Ethernet

Model	i210-T1	Dual Port Copper= I350-T2V2 Dual Port LC-Fiber= I350-F2	Dual Port Copper= I350-T4 V2 Dual Port LC-Fiber= I350-F4	Dual Port Copper= X540-T2	X710-DA2
Connector	RJ-45 Copper	2 x Ports RJ-45 Copper or 2 x Ports LC-Fiber	4 x Ports RJ-45 Copper or 4 x Ports LC-Fiber	2 x Ports RJ-45 Copper	2 x SFPs Receptable
Website	i210 T1	i350 T2/F2	i350 T4/F4	x540 T2	x710 DA2
Auto-Negotiation	IEEE* 802.3* Auto-negotiaton	IEEE* 802.3* Auto-negotiaton	IEEE* 802.3* Auto-negotiaton	IEEE* 802.3* Auto-negotiaton	IEEE* 802.3* Auto-negotiaton
Intel® vPro™	Not Available	Not Available	Not Available	Not Available	Not Available
Intel® Standard Manageability	Supported	Supported	Supported	Supported	Supported
Power Optimizer Platform Low-power Management Systems	Supported	Supported	Supported	Supported	Supported
Energy Efficient Ethernet	Supported	Supported	Supported	Not Available	Supported
TCP/UDP Checksum and Segmentation Offload (IPv4 and IPv6)	Supported	Supported	Supported	Supported	Supported
Receive Side Scaling	Supported	Supported	Supported	Supported	Supported
Dual Tx and Rx Queues	Yes	Yes	Yes	Yes	Yes
Jumbo Frames (up to 9KB)	Supported	Supported	Supported	Not Available	Supported
Teaming	Not Available	Supported	Supported	Supported	Supported
Wake from Deep Sx	Supported	Supported	Supported	Not Available	Not Available
Server Operating System Support	Windows Server 2008, 2012, 2016, 2019 Linux (RHEL/SLES), Free BSD, Xen, Vmware	Windows Server 2008, 2012, 2016, 2019 Linux (RHEL/SLES), Free BSD, Xen, Vmware	Windows Server 2008, 2012, 2016, 2019 Linux (RHEL/SLES), Free BSD, Xen, Vmware	Windows Server 2003, 2008; RHEL 4, Linux/SLES 11, Vmware	Windows 2008, 2012; RHEL 6.5/7.0, FreeBSD 9/10, Vmware ESXi 5.x

Network Proxy/ARP Support	Supported	Supported	Supported	Supported	Supported
---------------------------	-----------	-----------	-----------	-----------	-----------

Ethernet

Model	AC 7260 NGW	AC 8265 NGW
Connector	2 x Antennas	2 x Antennas
Website	7260 NGW	8265 NGW
Auto-Negotiation	Not Available	Not Available
Intel® vPro™	Supported	Supported
Intel® Standard Manageability	Not Available	Not Available
Power Optimizer Platform Low-power Management Systems	Supported	Supported
Energy Efficient Ethernet	Not Available	Not Available
TCP/UDP Checksum and Segmentation Offload (IPv4 and IPv6)	Not Available	Not Available
Receive Side Scaling	Not Available	Not Available
Dual Tx and Rx Queues	Not Available	Not Available
Jumbo Frames (up to 9KB)	Not Available	Not Available
Teaming	Not Available	Not Available
Wake from Deep Sx	Not Available	Not Available
Server Operating System Support	Not Available	Not Available
Network Proxy/ARP Support	Not Available	Not Available

Media Card Reader

Description	9-in-1 (USB 2.0)
-------------	------------------

SECTION IV:

BIOS/Certifications/Standards/Environmental

BIOS Specifications

--	--

WMI Support	Compliant With Microsoft WBEM and the DMTF Common Information Model
ROM-Based Setup Utility (F1)	System Configuration Setup Program (text only interface) Available at Power-on With F1 Key
Bootblock Recovery	Recovers System BIOS if the Flash ROM Becomes Corrupted
Replicated Setup	Saves System Configuration Settings to a File That Can Then be Used to Replicate the Settings to Other Systems
Boot Control	Boot Control Available Through ROM-based Setup Utility or With F12 Key at Power-on
Memory Change Alert	Power-on Error Message in the Event of a Decrease in System Memory
Thermal Alert	Power-on Error message in the Event of a Fan Failure
Asset Tag	Supports Ability to Set SMBIOS Type 2 Baseboard Asset Tag Field
System/Emergency ROM Flash Recovery With Video	Supports Process to Recover the System BIOS if the Flash ROM Becomes Corrupted
Remote Wakeup/Remote Shutdown	System Admin Can Power On/Off a Client Computer from a Remote Location to Provide Maintenance
Quick Resume Time	Supports Low Power S3 (suspend to RAM) and Prompt Resume Times
ROM Revision Level	System UEFI (BIOS) Version Reported in SMBIOS Type 0 Structure and in BIOS Setup
Keyboard-less Operation	System Can be Booted Without a Keyboard
Per-port Control	Allows I/O Ports to be Individually Enabled/Disabled Through ROM-based Setup or WMI Interface
Adaptive Cooling	Offers Multiple Settings for Fan Control Ranging Between Better Performance and Better Acoustics
Security	User and Administrator Passwords Can Protect Boot and ROM-based Setup <ul style="list-style-type: none"> - Support Electronic Lock - Chassis Intrusion Detection - UEFI Secure Boot Support - HDD Password Can Protect HDD Data - Windows UEFI Firmware Update Support - Device Guard Support - Optional Access Panel Lock, Kensington Lock, and Pad Lock
Intel(R) AMT (includes ASF 2.0)	Allows System to be Supported from a Remote Location
Intel(R) TXT	Intel(R) Trusted Execution Technology Provides a Security Foundation to Build Protections Against Software Based Attacks
Memory Modes	Supports Mirroring, Lock Step, and Sparing Memory Modes
Windows 10 Ready	Supports Windows 10 Requirements for Secure Flash, UEFI v 2.6 Device Guard Support Spec

Industry Standard Specification Support

UEFI	Unified Extensible Firmware Interface v2.7
ACPI (Advanced Configuration and Power management Interface)	Advanced Configuration and Power Interface v6.1
ASF 2.0	DMTF Alert Standard Format Specification v2.0
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6)

CD Boot	EI Torito Bootable CD-Rom Format Specification, v1.0
EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision v1.0
PCI	NA (No PCI slot)
PCI Express	PCI Express Base Specification v3.0
SATA	Serial ATA Revision 3.0 Specification
TPM	Trusted Computing Group TPM Specification v2.0
UHCI	Universal Host Controller Interface Design Guide, Revision v1.1
USB	Universal Serial Bus Revision v1.1 Universal Serial Bus v2.0 Universal Serial Bus v3.0
SMBIOS	DMTF System Management Spec v3.2.1
XHCI	XHCI SPEC Revision v1.2

Social and Environmental Responsibility

Quality Control	Lenovo is a member of an eco declaration system that enforces regular independent quality control
Hazardous Substances and Preparation	<ul style="list-style-type: none"> • Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1) • Products do not contain Asbestos • Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide • Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparation • Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP • Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week <p>REACH Article 33 information about substances in articles is available at: http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment</p>
Batteries	Not Available
Safety, EMC Connection to the Telephone Network and Labeling	Not Applicable, no Connection to a Telephone Network

Safety, EMC Connection to the Telephone Network and Labeling

System Software Manager	Lenovo ThinkStation Supports Software Management Tools by Lenovo Vantage
-------------------------	--

Regulations & Standards

EMC & Safety	<p>FCC DoC for North America VCCI Certification for Japan BSMI Certification for Taiwan EU/EFTA CE Mark & DoC UL/CUL(P920,P720,P520,P520c), cTUVus(P330) UL-GS(P920,P720,P520,P520c), TUV-GS(P330) IEC60950-1 CB Report/Certificate Saudi Arabia SASO Kuwait KUCAS China CCC Mark Hong Kong SAR (CB report) Singapore PSB South Africa SABS Russia-EAC Morocco-CM Mexico-NOM Kazakhstan-EAC Belarus-EAC Serbia KVALITET Ukraine UKrCEPRO India-BIS USA Chemical Emission Test</p>
--------------	--

Environmentals

Energy Star	ENERGY STAR® v7.0
EPEAT	EPEAT® Silver Certification Available on Select Models
Greenguard	Greenguard
RoHs	RoHS Compliant
ErP Lot-3 2013	Yes
Hazardous Substances	<ul style="list-style-type: none"> • Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenol ethers (PBDE) • Products do not contain Asbestos • Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide • Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparation • Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP • Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm₂/week
Disclaimers	EPEAT registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country.