

# Lenovo ThinkPad P14s Gen 4 AMD

Version: 5.0 | 05/22/2024

---

Product Name	P14s Gen 4 AMD
Product Display Name	P14s Gen 4 AMD
Information Date	27-Feb-24

## SECTION I: Platform Overview

---

Description	<p>The Lenovo ThinkPad P14s, our thinnest and lightest mobile workstation, offers on-the-go performance at a comfortable price point, all in a 14-inch chassis with an optimized 16:10 display. Built with the latest AMD processors and integrated graphics, the P14s is ISV certified, powering applications such as AutoCAD®, Revit® and SolidWorks® without missing a beat. Perfect for highly mobile power users with an advanced suite of ThinkShield security features and comprehensive MIL-SPEC testing for ultimate durability, the P14s gives entry-level professionals, educators, and students alike the ability to innovate freely wherever life takes you.</p>
-------------	---

## CPU

Processor Support	AMD Phoenix Ryzen 7 PRO 7840U Processor AMD Phoenix Ryzen 5 PRO 7540U Processor
Socket Type	BGA

## Operating Systems

Preloaded	Windows 11 Pro 64 (22H2) Windows 11 Home 64 Windows 11 Home Single Language 64 Windows 11 Home Chinese Language Edition 64 CMIT Government Edition Ubuntu (Version22.04)
-----------	---

Supported	Windows 11 Pro 64 (22H2) Windows 11 Home 64 Windows 11 Home Single Language 64 Windows 11 Home Chinese Language Edition 64 CMIT Government Edition Ubuntu (Version22.04)
-----------	---

## Memory

Number of DIMM Slots	No
Channels	Dual Channel LPDDR5x
Type	LPDDR5x
ECC Support	No
Speed	6400 MHz
Max DIMM Size	64GB
Max System Memory	64GB
Min System Memory	16GB
Soldered Memory	16GB/32GB/64GB

## Storage

Storage Slots	1 x PCIe Gen 4 M.2 2280
SATA	/
PCIe	Solid State Drive, OPAL2 PCIe-NVMe Gen 4 M.2 2280- TLC
SAS	None
Interface	PCIe Gen 4
Security	PCIE
Optional Hard Disk Drive Controllers	OPAL2 for NVMe SSD

## Video

Integrated Graphics	AMD Radeon™ Graphics
Discrete Graphics	N/A
Adapter	None
Bus Interface	NA

## Display

Resolutions	FHD+ / 2.8k OLED
-------------	------------------

## Camera

Resolution	720p HD/1080p FHD/5MP
Frames per Second	30 fps
Focus	Fixed 50cm
Camera Interface	USB 2.0
IR Camera	Yes (optional)

## Keyboard

Number of Keys	US : 84 / UK : 85 / JP : 89
Numpad	No
Size	100% ISO
Function Key Features	Yes
Backlit	Yes
Keyboard size	CS22 Top mount 14" KBD with shrunken letter keys
Key stroke	1.5mm
Key pitch	19.05mm
Keyboard backlight	Optional
Keyboard thickness	Standard

## TrackPad / Fingerprint Reader

TrackPoint Details	COMO TrackPoint module (t5.5mm)
Finger Print Reader Model	Synaprics Metallica 8x8 FPR, MoC
Multi-Touch	Yes
Resolution	1000 ppi
TrackPad/TouchPad thickness	3.3mm
TrackPad/TouchPad type	3 BCP
TrackPad size	115mm x 61 mm
TrackPad material/finish	Mylar surface

## I/O – Ports and Connectors

USB	2x USB-A (5Gbps) (1 powered)
Thunderbolt	1x USB 4.0 and 1x USB-C® (10Gbps)
HDMI	1x HDMI 2.1 up to 4K/60Hz
Audio Combo Jack	1x Microphone & Headphone Combo Jack (3.5mm)

Media Card Reader	N/A
Smart Card Reader	Yes (optional)
Power Connector	DC-In
Docking Port	2x USB-C® (Thunderbolt™ 4)
VirtualLink	None
Network adapter	Gigabit Ethernet (RJ45)
Disclaimers	HDMI 2.1: Up to 8K/60Hz

## Power Connector

Main	DC-In
USB-C	1x USB 4.0 and 1xUSB-C® (10Gbps)

## Ethernet

Vendor	Realtek
Count	x1
EEPROM	SPI ROM (Merge with BIOS/MEFW)
Speeds	10/100/1000 Mbps
Functions	Wake On LAN MAC Address Pass Through PXE Boot Flash Over LAN
Connectors	RJ45

## WWAN

Model	optional: CAT16/CAT4 with physical eSIM optional
-------	--

## Near Field Communications

Model	Yes, optional
-------	---------------

## Audio

Vendor	Realtek
Type	High Definition Audio Codec
Internal Speaker	Yes, dual speakers
Connectors	Microphone & Headphone Combo Jack (3.5mm)

Chipset	ALC3287
Number of Channels	4-channel DAC, 4-channel ADC
Number of Bits/Audio Resolution	16/20/24-bit PCM format
Sampling Rate (Recording/Playback)	n
Signal to Noise Ratio	90dB Signal-to-Noise Ratio (A-weighting) for ADC input. 100dB Signal-to-Noise Ratio (A-weighting) for DAC output
Analog Audio	None
Dolby Digital	Yes
Digital Out (S/PDIF)	No
Speaker Power Rating	2W@4ohm/ch

## Power adapter

Type	65W AC Slim Adapter	65W AC Adapter	r
Dimensions	88mm x 51mm x 22mm		108.5mm x 46.5mm x 29.5mm
Input Voltage	100-240V		100-240V

## Security

TPM	Yes, TPM2.0
Asset ID	Yes
vPro	Yes

## Chassis Information

Format	Ultraslim Notebook
Color	Thunder Black/Storm Grey
Thermal Solutions	Internal Single FAN, Intelligent Cooling
Dimensions	Length 12.50 inches 317.7 millimeters Width 8.93 inches 226.9 millimeters 21.8 mm (design value) 17.9 mm (Mkt claim) 0.85 in (design value) 0.70 in (Mkt claim)
Weight	Starting weight 1.34kg / 2.97 lbs

## Packaging Parameters

Height (mm)	300
-------------	-----

Height (inch)	11.8
Width (mm)	446
Width (inch)	17.6
Depth (mm)	81
Depth (inch)	3.1
Weight (kgs)	0.32kg
Weight (lbs)	0.71lbs

## Security & Serviceability

Self Healing BIOS	Yes
Access Panel	Removeable bottom cover
Number of Screws	6
Swappable Components	Base cover assembly, TrackPoint pointing stick, Lenovo factory recovery USB key, Power cord, ac power adapter (65W)
Storage Slots	1 storage slot
Memory	1 soldered down RAM
System Board	I190 System Board. No self-service CRU.
Restore CD/DVD/USB Set	None. Purchase via Lenovo Customer Support Center
Cable Lock Support	Security-lock slot
Power-On Password	Yes
Hard Disk Password	Yes; User and Master hard disk password
Supervisor Password	Yes
NIC LEDs (integrated)	Yes (if it means the LED for Ethernet)
Security Chip	Yes (for TPM 2.0)
Access Panel Key Lock	Bottom Cover Tamper Detection
Boot Sequence Control	Yes

## Operating Environment

Operating – Air Temperature	At altitudes up to 2438 m (8000 ft) – Operating: 5°C to 35°C (41°F to 95°F)
Non Operating – Air Temperature	At altitudes up to 2438 m (8000 ft) – Storage: 5°C to 43°C (41°F to 109°F)
Humidity	Operating: 8% to 95% at wet-bulb temperature 23°C (73°F) Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)
Corrosive Gas	G1
Particulates	P1

## SECTION II: Platform Detail

---

### Supported Components

Processor	AMD Phoenix Ryzen 7 PRO 7840U Processor AMD Phoenix Ryzen 5 PRO 7540U Processor
Memory Support	LPDDR5x 6400MHz
Chipset (PCH)	Integrated Soc
Size of BIOS Flash	64 MB
Super I/O	N/A
Clock	Crystal
Audio	Realtek High Definition Audio
Ethernet	Realtek RTL8111EPV

### Memory

System Capacity Options	16/32GB/64GB soldered-down
non-ECC	16/32GB/64GB soldered-down
Brand of non-ECC Memory	Samsung SK Hynix Micron
ECC	None
Brand of ECC Memory	N/A
Memory clock frequency(MHz)	LPDDR5x 6400 MHz

### Storage

2.5" SAS Hard Disk Drive (HDD)	None
2.5" SATA Hard Disk Drive (HDD)	None
2.5" SATA Solid State Drive (SSD)	None
M.2 (NGFF) PCIe Solid State Drive (SSD)	256GB Opal 2 PCIe G4 NVMe M.2 2280 512GB Opal 2 PCIe G4 NVMe M.2 2280 512GB Opal 2 PCIe G4 NVMe Performance M.2 2280 1TB Opal 2 PCIe G4 NVMe M.2 2280 1TB Opal 2 PCIe G4 NVMe Performance M.2 2280 2TB Opal 2 PCIe Gen4 Performance NVMe M.2 2280
2.5" PCIe Solid State Drive (SSD)	None
Brand of Drive	Samsung UnionMem WD

	Hynix Kioxia
Intel Optane Storage Technology	Yes
RAID	Not Supported

## Removeable Media

Media Card Reader Specifications	N/A
----------------------------------	-----

## SECTION III: Supported Component Detail

---

### CPU Specifications

CPU	AMD Phoenix Ryzen 5 PRO 7540U Processor	AMD Phoenix Ryzen 7 PRO 7840U Processor
Integrated Graphics	AMD Radeon™ Graphics + AMD Pro APU Driver	AMD Radeon™ Graphics + AMD Pro APU Driver
# of Cores	6 cores	8 cores
# of Threads	12	16
Processor Base Frequency	3.2GHz	3.3GHz
Max Turbo Frequency	4.9GHz	5.1GHz
Cache	22MB	24MB

### Display Specifications

Model	WUXGA	WUXGA oncell touch	WUXGA low power	WUXGA ePrivacy	2.8k
Resolution	1920 x 1200	1920 x 1200	1920 x 1200	1920 x 1200	2880 x 1800
Diagonal	14"	14"	14"	14"	14"
Aspect Ratio	Ratio 16:10	Ratio 16:10	Ratio 16:10	Ratio 16:10	Ratio 16:10
Backlight	LED	LED	LED	LED	None
PPI	162	162	162	162	243
Active Area	302 x 188	302 x 188	302 x 188	302 x 188	302 x 188
Refresh Rate	60 Hz	60 Hz	60 Hz	60Hz	60 Hz
Contrast Ratio	800:1 (TYP)	800:1 (TYP)	1000:1 (TYP)	1500:1 (TYP)	100000:1 (TYP)
Viewing Angle	85/85/85/85 degree	85/85/85/85 degree	85/85/85/85 degree	85/85/85/85 degree	85/85/85/85 degree
Color gamut	45% NTSC	45% NTSC	100% sRGB	100% sRGB	100% DCI-P3



Brightness	300nit	300nit	400nit	500nit	400nit
Contrast	Ratio 800:1	Ratio 800:1	Ratio 1000:1	Ratio 1500:1	Ratio 100000:1
Color Depth	16M	16M	16M	16M	1074M
Interface	eDP 1.2	eDP 1.2	eDP 1.4	eDP 1.4	eDP 1.4
Panel ID Recognition	EDID in BIOS Table	EDID in BIOS Table	EDID in BIOS Table	EDID in BIOS Table	EDID in BIOS Table
Weight	305g max	310g max	245g max	270g max	180g max
Color Calibrator	None	None	Adaptive ICC profile	None	X-Rite Factory Color Calibration, Dolby Vision
Panel Technology	IPS, Anti-Glare	IPS, Anti-Glare	IPS, Anti-Glare, LBL, Eyesafe certified	IPS, Anti-Glare	OLED, Anti-Glare/Anti-reflection/Anti-fingerprint, LBL, Eyesafe certified
Touch Panel	None	YES	None	YES	None

## HDD Specifications

2.5" SAS Hard Disk Drive (HDD)	N/A
2.5" SATA Hard Disk Drive (HDD)	N/A

## HDD Storage Device Specifications

Connector	N/A
Transfer Rate (Gb/sec)	N/A

## HDD Performance

Spindle Speed(RPM)	N/A
Power off to Spindle Stop(sec)	N/A
DC Power to Drive Ready(sec)	N/A
Receipt of Start Unit Command to Drive Ready(sec)	N/A
Average Latency(msec)	N/A

## HDD Power Management

Input (VDC)	N/A
Typical (Watts)	N/A
Idle (Watts)	N/A

## HDD Dimensions

Height (mm – Max)	N/A
Width (mm)	N/A
Depth (mm – Max)	N/A
Weight (grams)	N/A

## HDD Temperature

Operating(C) Ambient	N/A
Operating(C) Base Casting	N/A
Non-Operating(C) Ambient	N/A
Gradient(C per Hour)	N/A

## HDD Shock

Operating(Gs @ 2ms)	N/A
Non-Operating(Gs @ 2ms)	N/A

## SSD Specifications

2.5" SATA Solid State Drive (SSD)	N/A
M.2 (NGFF) PCIe Solid State Drive (SSD)	1x M.2 2280 PCIe Gen4
2.5" PCIe Solid State Drive (SSD)	N/A
Intel Optane Storage Technology	N/A

## Solid State Storage Devices

Supported Types	M.2
Dimensions inches/centimeters (W x D x H)	22.0 (+-0.15) x 80.0 (+-0.15) x 2.3 (max)

H)	
Size	M.2 2280S3
Interface Type	PCIe NVMe Gen4
Read/Write IOPS Specifications	Performance PCIe Gen4 Read: 700k (2TB), 600k (1TB) Write: 600k (2TB, 1TB) Value PCIe Gen4 Read: 300k (1TB), 250k (512GB), 200k (256GB) Write: 240k (1TB, 512GB), 190k (256GB)
Bandwidth Performance	PCIe Gen4 x 4 (16Gbps)
Power Consumption (Max)	3.0A (10us average)
Active(AVG)	5W
Idle	5mW (L1.2)
Min MTBF	2'000'000
Min Sequential Read	Performance PCIe Gen4 6400MB/s (2TB, 1TB) Value PCIe Gen4 3500MB/s (1TB, 512GB), 3200MB/s (256GB)
Min Sequential Write	Performance PCIe Gen4 5000MB/s (2TB), 4400MB/s (1TB) Value PCIe Gen4 2900MB/s (1TB), 2500MB/s (512GB), 1800MB/s (256GB)
Hardware Encryption	Yes

## Discrete Graphics Adapter

GPU Name	N/A
CUDA Processing Cores	N/A
GPU Memory	N/A
Memory Bandwidth	N/A
Memory Type	N/A
Memory Interface	N/A
TGP Max Power Consumption	N/A
Display Port	N/A
OpenGL	N/A
Shader Model	N/A
DirectX	N/A
PCIe Generation	N/A
Floating-Point Performance	N/A
VR Ready	N/A
Simultaneous Multi-Projection	N/A
NVIDIA FXAA/TXAA Antialiasing	N/A

NVIDIA nView Display Management Technology	N/A
GPU Direct for Video	N/A
Vulkan Support	N/A
NVIDIA Optimus	N/A

## WLAN

Model	Qualcomm NFA-725A onboard	Mediatek RZ616 onboard
Connector: Main, Aux/GNSS, GNSS	ANT1:AUX WiFi + BT; ANT2: Main WiFi	Coming Soon
Antenna Diversity	Supported	Coming Soon
MIMO	Not supported	Coming Soon
GNSS Band	N/A	Coming Soon
Radio ON/OFF Control	Supported	Coming Soon
Connector interface	PCIE	Coming Soon
Operating Temperature (Adapter Shield)	0c to +80c	Coming Soon
Humidity Non-Operating	50%~90% Rh non condensing (at temperatures of 25c to 35c)	Coming Soon
Operating Systems	Microsoft Windows 7*, Microsoft Windows 8.1*, Microsoft Windows 10*, Linux* (limited feature support), Android	Coming Soon
Wi-Fi Alliance	Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM-PS*, WPA*, WPA2*, WPS2*, Protected Management Frames, Wi-Fi Direct* for peer to peer device connections, Wi-Fi Miracast* as Source.	Coming Soon
IEEE WLAN Standard	IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending OS support; Fine Timing Measurement based on 802.11REVmc	Coming Soon
Roaming	Support seamless roaming between access points	Coming Soon
Bluetooth*	Dual Mode Bluetooth® 5.0, BLE	Coming Soon
Authentication	WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA, EAP-AKA	Coming Soon
Authentication Protocols	PAP, CHAP, TLS, MS-CHAP*, MS-CHAPv2	Coming Soon
Encryption	64-bit and 128-bit WEP, 128-bit AES-CCMP	Coming Soon
Regulatory	For a list of country approvals, please contact your local Intel representatives.	Coming Soon
US Government	FIPS10, FISMA	Coming Soon

Product Safety	UL,C-UL,CB (IEC 60950-1)	Coming Soon
Disclaimers	Bluetooth may be limited by OS	Bluetooth may be limited by OS

## Battery

Dimension	270 mm x 68.5 mm x 6.16 mm	270 mm x 68.5 mm x 6.16 mm
Weight	173g	212g
Type (Chemistry and Cell)	Li-ion Polymer	Li-ion Polymer
Voltage	11.58V ~ 11.61V	15.44V ~ 15.48V
Battery Capacity	Integrated 3-cell 39.3Wh battery	Integrated 4-cell 52.5Wh battery
Charging Time	0% to 100% 0% to 80% Battery Charging Time (in-operation) 2.06 hr Battery Charging Time (off) 1.89 hr 0.92 hr	0% to 100% 0% to 80% Battery Charging Time (in-operation) 2.39hr Battery Charging Time (off) 1.98 hr 0.99 hr
Operating Temperature Range	between 10°C (50°F) and 35°C (95°F)	between 10°C (50°F) and 35°C (95°F)
Warranty	1 Year / 3 Year Available	1 Year / 3 Year Available
Coin Cell Battery (Model)	CR2016	CR2016

## SECTION IV: BIOS / Certifications / Standards / Environmental

---

### BIOS Specifications

WMI Support	Yes, if it is BIOS Setup change by WMI.
ROM-Based Setup Utility (F1)	Yes
Bootblock Recovery	N/A
Replicated Setup	Yes, it supported with SRSETUP tool.
Boot Control	Yes, it means Boot order change.
Memory Change Alert	N/A
Thermal Alert	N/A
Asset Tag	Yes
System/Emergency ROM Flash Recovery with Video	N/A
Remote Wakeup/Remote Shutdown	Yes, if Remote wakeup is Wake on LAN from S4/S5.
Keyboard-less Operation	N/A
Per-port Control	Yes, if it is I/O port enable/disable by BIOS Setup.
Adaptive Cooling	Yes, if it is thermal & fan control.

Security	Yes, BIOS password / Hard disk password / Finger print
Intel(R) AMT (includes ASF 2.0)	Yes. If you select vPro model
Intel(R) TXT	Yes. If you select vPro model
Memory Modes	N/A

## EMC & Safety

EMC	<p>Published, Certified Existing Reports</p> <p>EMC – Australia  EMC – Belarus  EMC – Canada  EMC – China  EMC – EU/EFTA  EMC – Japan  EMC – Kazakhstan  EMC – New Zealand  EMC – Russia  EMC – South Korea  EMC – Taiwan  EMC – USA/Territories  Not Applicable / Not Required  EMC – Israel  EMC – Moldova  EMC – Serbia  EMC – Turkey  EMC – Uzbekistan  EMC – Vietnam</p>
Safety	<p>To access the latest User Guide and Safety and Warranty Guide, go to:  <a href="https://support.lenovo.com">https://support.lenovo.com</a>  Low Halogen Declaration of Conformance  TNOT-2017-0040  Section 9 – Low Halogen Scorecard  Izod Test – EPEAT Compliant  Homologation PCRB Compliant  In the following countries: Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Azerbaijan, Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belize, Benin, Bermuda, Bolivia, Botswana, Burkina Faso, Burundi, Cambodia, Cameroon, Canada, Cape Verde, Cayman Islands, Central African Republic, Chad, China, Colombia, Comoros, Congo, Costa Rica, Djibouti, Dominican Republic, Egypt, El Salvador, Eritrea, Ethiopia, EU/EFTA, Fiji, Gabon, Gambia, Georgia, Ghana, Grenada, Guatemala, Guinea, Haiti, Honduras, Hong Kong, India, Indonesia, Israel, Jamaica, Japan, Jordan, Kazakhstan, Kenya, Kuwait, Laos, Lebanon, Liberia, Macau, Madagascar, Malawi, Malaysia, Mali, Mauritania, Mauritius, Mexico, Moldova, Mongolia, Morocco, Mozambique, Namibia, Nepal, New Zealand, Nicaragua, Niger, Nigeria, Oman, Pakistan, Panama, Papua New Guinea, Paraguay, Peru, Philippines, Qatar, Russia, Saudi Arabia, Senegal, Serbia, Seychelles, Sierra Leone, Singapore, South Africa, South Korea, Sri Lanka, Swaziland, Taiwan, Tajikistan, Tanzania, Thailand, Togo, Tunisia, Turkey, Turkmenistan, Uganda, Ukraine, United Arab Emirates, Uruguay, USA/Territories, Uzbekistan, Venezuela, Vietnam, Zambia, Zimbabwe, Brazil – Inmetro 170 Govt Bids, Guinea-Bissau, Lesotho</p>

## Environmentals

Energy Star	<p>ENERGY STAR® Version 8.0  For more information about ENERGY STAR, go to:  <a href="https://www.energystar.gov">https://www.energystar.gov</a></p>
EPEAT	EPEAT Declaration of Conformance For Machine Types: 20S4, 20S5

IT ECO declaration	The latest environmental information about Lenovo products is available at: <a href="https://www.lenovo.com/ecodeclaration">https://www.lenovo.com/ecodeclaration</a>
Hazardous Substances	The latest environmental information about Lenovo products is available at: <a href="https://www.lenovo.com/ecodeclaration">https://www.lenovo.com/ecodeclaration</a> European Union RoHS This Lenovo product, with included parts (cables, cords, and so on) meets the requirements of Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("RoHS recast" or "RoHS 2"). For more information about Lenovo worldwide compliance on RoHS, go to: <a href="https://www.lenovo.com/rohs-communication">https://www.lenovo.com/rohs-communication</a>

## Manageability

Industry Standard Specifications	This product meets the following industry standard specifications for manageability functionality: Intel LAN with AMT
Remote Manageability Software Solutions	Lenovo ThinkManagement Console Microsoft System Center Configuration Manager LANDesk Management Suite for ThinkVantage Technologies ( <a href="http://www.landesk.com/lenovo">www.landesk.com/lenovo</a> )
System Software Manager	Lenovo ThinkPad supports software management tools from the Lenovo Vantage System Update suite: System Update Update Retriever
Service, Support, and Warranty	On-site Warranty and Service: Three-years, limited warranty and service offering delivers on-site, next business-day service for parts and labor and includes free telephone support 8am to 5pm. Global coverage ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.

## Environmentals

Energy Star	ENERGY STAR® 8.0
EPEAT	EPEAT® Gold
RoHS Compliant	RoHS Compliant
TCO	TCO 9.0
Sustainability	97% PCC recycled plastic: Speaker enclosure 97% recycled plastic: 52.5Whr Battery 95% PCC recycled plastic: 65W PSU 90% recycled/sustainable packaging Low-temperature solder
Disclaimers	Product packaging shall contain, on average, a minimum total percentage of 90% by weight of any combination of the following materials: Recycled content, biobased plastic, non-wood biobased fiber material, and/or sustainably forested material.